

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WD-40 3-IN-ONE PROFESSIONAL SILICONE

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Application is by spray atomisation from a hand held aerosol pack. Silicone lubricant spray.

SUPPLIER

Company: WD- 40 Company
Address:
41 Rawson Street
Epping
NSW, 2121
AUS
Telephone: +61 2 9868 2200
Fax: +61 2 9869 7512

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Extremely flammable.
Irritating to skin.
Risk of explosion if heated under confinement.
Vapours may cause drowsiness and dizziness.

SAFETY

Keep away from sources of ignition. No smoking.
Do not breathe gas/ fumes/ vapour/ spray.
Wear eye/ face protection.

Use only in well ventilated areas.

Keep container in a well ventilated place.
To clean the floor and all objects contaminated by this material use water and detergent.
Keep container tightly closed.
Take off immediately all contaminated clothing.
In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).
This material and its container must be disposed of as hazardous waste.

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 2 of 11

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
distillates, petroleum, light, hydrotreated	64742-47-8	35-40
white spirit	8052-41-3.	25-30^
polydimethylsiloxane	63148-62-9	2-4^
hydrocarbon propellant	68476-85-7.	25-35^

Section 4 - FIRST AID MEASURES

SWALLOWED

- Avoid giving milk or oils.
Avoid giving alcohol.
Not considered a normal route of entry.
- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.

EYE

- If aerosols come in contact with the eyes:
- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
- Flush skin and hair with running water (and soap if available).
 - Remove any adhering solids with industrial skin cleansing cream.
 - DO NOT use solvents.
 - Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
- Remove to fresh air.
 - Lay patient down. Keep warm and rested.
 - Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
 - Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet

Issue Date: 6-May-2008

NC317ECP

CHEMWATCH 4944-64

Version No:5

CD 2008/2 Page 3 of 11

Section 4 - FIRST AID MEASURES

- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]. Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

SMALL FIRE:

- Water spray, dry chemical or CO₂

LARGE FIRE:

- Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition with violent container rupture.
- Aerosol cans may explode on exposure to naked flames.
- Rupturing containers may rocket and scatter burning materials.
- Hazards may not be restricted to pressure effects.
- May emit acrid, poisonous or corrosive fumes.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 4 of 11
Section 5 - FIRE FIGHTING MEASURES

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 2Y

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES


MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)
Isolation Distance -

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet

Issue Date: 6-May-2008

NC317ECP

CHEMWATCH 4944-64

Version No:5

CD 2008/2 Page 5 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

Downwind Protection Distance 8 metres
IERG Number 49

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 126 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 6 of 11
Section 7 - HANDLING AND STORAGE

internal pressure may eject contents of can.

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
Australia Exposure Standards	white spirit (White spirits)		790
Australia Exposure Standards	hydrocarbon propellant (LPG (liquified petroleum gas))	1000	1800

The following materials had no OELs on our records

- distillates, petroleum, light, hydrotreated: CAS:64742- 47- 8
- polydimethylsiloxane: CAS:63148- 62- 9

MATERIAL DATA

Not available. Refer to individual constituents.

INGREDIENT DATA

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
 - cause increased susceptibility to other irritants and infectious agents
 - lead to permanent injury or dysfunction
 - permit greater absorption of hazardous substances and
 - acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.
- for petroleum distillates:

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

CEL TWA: 500 ppm, 2000 mg/m³ (compare OSHA TWA).

Human exposure to oil mist alone has not been demonstrated to cause health effects except at levels above 5 mg/m³ (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

CEL TWA: 300 ppm, 2100 mg/m³

PERSONAL PROTECTION

EYE

No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

HANDS/FEET

No special equipment needed when handling small quantities.

OTHERWISE:

For potentially moderate exposures:

Wear general protective gloves, eg. light weight rubber gloves.

For potentially heavy exposures:

Wear chemical protective gloves, eg. PVC. and safety footwear.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards")

Protection Factor (Min)	Half- Face Respirator	Full- Face Respirator
10 x ES	Air- line*	AX- P- - 2 AX- P- - PAPR- 2
20 x ES	-	AX- P- - 3
20+ x ES	-	Air- line**

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.
For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 8 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.
Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant.
Clear liquid with a petroleum odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.
Gas.
Does not mix with water.
Floats on water.

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Immiscible
pH (1% solution): Not Applicable
Volatile Component (%vol): 98
Relative Vapour Density (air=1): Not Applicable
Lower Explosive Limit (%): 1.8
Autoignition Temp (°C): Not Available
State: Liquid

Boiling Range (°C): Not Available
Specific Gravity (water= 1): 0.75
pH (as supplied): Not Applicable
Vapour Pressure (kPa): 40- 60 PSI @ 21C
Evaporation Rate: Not Available
Flash Point (°C): - 29 (TOC)
Upper Explosive Limit (%): 9.5
Decomposition Temp (°C): Not Available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5
CD 2008/2 Page 9 of 11

Section 11 - TOXICOLOGICAL INFORMATION

SKIN

This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

Aromatic hydrocarbons may produce sensitivity and redness of the skin. They are not likely to be absorbed into the body through the skin but branched species are more likely to.

INHALED

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

Exposure to white spirit may cause nausea and vertigo.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

CHRONIC HEALTH EFFECTS

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

WARNING: Aerosol containers may present pressure related hazards.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet
Issue Date: 6-May-2008
NC317ECP

CHEMWATCH 4944-64
Version No:5

CD 2008/2 Page 10 of 11

Section 12 - ECOLOGICAL INFORMATION

under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS
HAZCHEM: 2Y

UNDG:

Dangerous Goods Class:	2.1	Subrisk:	None
UN Number:	1950	Packing Group:	None
Shipping Name:	AEROSOLS		

Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	None
Special provisions:	A145 A153		
Shipping Name:	AEROSOLS, FLAMMABLE		

Maritime Transport IMDG:

IMDG Class:	2.1	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D, S- U	Special provisions:	63 190 277 327 959
Limited Quantities:	See SP277	Marine Pollutant:	Not Determined
Shipping Name:	AEROSOLS		

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

continued...

WD-40 3-IN-ONE PROFESSIONAL SILICONE

Chemwatch Material Safety Data Sheet

Issue Date: 6-May-2008

NC317ECP

CHEMWATCH 4944-64

Version No:5

CD 2008/2 Page 11 of 11

Section 15 - REGULATORY INFORMATION

REGULATIONS

WD-40 3-In-One Professional Silicone (CAS: None):

No regulations applicable

distillates, petroleum, light, hydrotreated (CAS: 64742-47-8) is found on the following regulatory lists;

Australia Hazardous Substances

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5

International Air Transport Association (IATA) Dangerous Goods Regulations

International Council of Chemical Associations (ICCA) - High Production Volume List

OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name

CAS

white spirit

8052- 41- 3, 8042- 47- 5

hydrocarbon propellant

68476- 85- 7, 68476- 86- 8

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 2100 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%)

Component	Breathing zone (ppm)	Breathing Zone (mg/m ³)	Mixture Conc (%)
distillates, petroleum, light, hydrotreated	300.00	2100.0000	40.0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 6-May-2008

Print Date: 6-May-2008